

IPACOLL® LP 2931 PB

Waterbased adhesive

DESCRIPTION	<p>IPACOLL® LP 2931 PB is a waterbased adhesive that has been designed for the bonding of cigarette hard boxes. IPACOLL® LP 2931 PB can be used on all fast running packing machines and should be applied by non contact nozzles (low pressure/small diameter).</p>												
PROPERTIES	<ul style="list-style-type: none">- good machinability- reduced skin building and no stringing on the nozzle- odourless- easy to clean- increased milage- high wet tack- plasticizer free												
REMARKS	<p>It is important to ensure that the desired level of adhesion is obtained on the necessary substrates, including long-term tests.</p>												
TYPICAL PROPERTIES	<table><tr><td>Colour</td><td>white</td></tr><tr><td>Film</td><td>elastic</td></tr><tr><td>Viscosity</td><td>Brookfield RV-Type: Sp 1/20rpm/20°C approx. 290 mPas</td></tr><tr><td>Solids</td><td>approx. 47.0 %</td></tr><tr><td>pH</td><td>approx. 4.5</td></tr><tr><td>Density</td><td>approx. 1.05 g/cm³ (20 °C)</td></tr></table>	Colour	white	Film	elastic	Viscosity	Brookfield RV-Type: Sp 1/20rpm/20°C approx. 290 mPas	Solids	approx. 47.0 %	pH	approx. 4.5	Density	approx. 1.05 g/cm ³ (20 °C)
Colour	white												
Film	elastic												
Viscosity	Brookfield RV-Type: Sp 1/20rpm/20°C approx. 290 mPas												
Solids	approx. 47.0 %												
pH	approx. 4.5												
Density	approx. 1.05 g/cm ³ (20 °C)												
SHELF LIFE	<p>In original sealed packaging at temperatures between 15 °C and 25 °C up to 6 months.</p>												
APPLICATION TYPE	<p>nozzle (eg HHS)</p>												
CLEANING	<p>Adhesive residues may be washed off with water.</p>												
HEALTH & SAFETY REGULATIONS	<p>See safety data sheet and label</p>												

IPACOLL[®] LP 2931 PB

Waterbased adhesive

PLEASE NOTE

The information, specified in this Product Information, is based on careful laboratory tests and prevailing practical experience.

The information is not binding, which is also generally true for our practical customer service, given verbally, in writing and by tests, since, on account of the versatility of applications and use, also including possible industrial property rights of third parties, we cannot assume any responsibility.

Analysis results and all information regarding state and suitability of our products are only guidelines with no obligation on our part, unless they have been guaranteed expressly in writing, and above all do not represent a guarantee for specific properties.

We advise determining the suitability of our products with respect to their suitability for the intended use and application technology by adequate further testing. In addition to the above, our General Sales and Delivery Conditions are applicable.

H.B. FULLER - EUROPE

H.B. Fuller Austria GesmbH

Phone: (43) (0) 7242 409 0
Fax: (43) (0) 7242 47296

H.B. Fuller Benelux B. V.

Phone: (B)0800 49 740/(NL)0800 020 3433
Fax: 00800 8882 8882

H.B. Fuller Italien S.r.l.

Phone: 0800 985 778
Fax: 0800 8882 8882

H.B. Fuller Europe GmbH

Phone: (41) (0) 44 315 77 00
Fax: (41) (0) 44 312 66 34

H.B. Fuller España S.A.

Phone: 800 099 493
Fax: 00800 8882 8882

H.B. Fuller Deutschland GmbH, Lbg

Phone: (49) (0) 4131 705 - 0
Fax: (49) (0) 4131 705 - 227

H.B. Fuller Deutschland Sp. z o.o.

Phone: (48) (0) 22 82 22 719
Fax: (48) (0) 22 668 54 65

H.B. Fuller Deutschland GmbH, Ni

Phone: (49) (0) 5021 88 - 0
Fax: (49) (0) 5021 88 - 224

H.B. Fuller France SAS

Phone: 0800-917537
Fax: 00800- 8882 8882

H.B. Fuller U.K. LTD

Phone: (44) (0) 161 666 0 666
Fax: (44) (0) 161 666 0 667

H.B. Fuller Sverige AB

Phone: (46) (0) 31 49 66 40
Fax: (46) (0) 31 49 13 26

H.B. Fuller, Isar-Rakoll S.A.

Phone: (351) (0) 229 288 200
Fax (351) (0) 229 288 290